



BDT Pty Ltd. Trading as **Rockstar Sealing Systems** ABN 18 085 322 390.
Head Office 3 Spray Avenue, Mordialloc 3195 Victoria, Australia.
Phone 1300 884 418 03) 9580 5510 **Fax** 03) 9580 5530
Web www.rockstarsealing.com.au **Email** info@rockstarsealing.com.au

NATURAL FINISH STONE SEALER

DESCRIPTION

Rockstar **NATURAL FINISH STONE SEALER** is a premium quality solvent-based sealer used to protect against staining on a wide variety of natural and man-made stones and tiles.

USES

NATURAL FINISH STONE SEALER is applied as the final sealing coat to help protect against staining due to oil and water-based substances such as cooking oils, red wine, and other everyday stain-inducing materials. The ingress of the staining substance is retarded, making the surface easier to clean.

BENEFITS

- Excellent oil and water repellency
- Does not change the surface appearance
- Does not inhibit the water-vapour permeability
- Ready to apply, no dilution required
- Rapid curing
- Cannot flake or peel

PROPERTIES

| | |
|------------------------------------|---|
| Appearance and colour..... | Colourless to yellowish, clear to hazy liquid |
| Specific Gravity (Water = 1) | 0.81 g/ml |
| Boiling Point | 120 - 200°C |
| Solubility in Water | Not miscible |
| Flash Point | 30°C |

APPLICATION INSTRUCTIONS

- 1) Always apply first to an inconspicuous area or scrap piece of stone to ensure the suitability of this product for your stone or tile.
- 2) Ensure the surface to be sealed is free of excess grout and grout haze, is dry and free of any oils and other surface contaminants.
- 3) Apply **NATURAL FINISH STONE SEALER** undiluted by lambswool applicator or low pressure hand sprayer. Ensure that the surface is fully saturated without leaving pools of material. Apply a second coat as soon as the first coat has dried (1-2 hours).
- 4) The product will cure in 6-18 hours depending on atmospheric conditions.

COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 8-10 Mt² per litre.

PRECAUTIONS

- 1) Do not allow pools of liquid **NATURAL FINISH STONE SEALER** to dry on the surface.
- 2) Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
- 3) Ensure that there are no sources of ignition in area.

CLEANING

Clean all equipment with mineral turpentine.

PACKAGING

NATURAL FINISH STONE SEALER is available in 1, 5 and 20 litre packs.

STORAGE

Keep container tightly closed when not in use.

Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.

DISCLAIMER

The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.