



BDT Pty Ltd. Trading as **Rockstar Sealing Systems** ABN 18 085 322 390.
Head Office 3 Spray Avenue, Mordialloc 3195 Victoria, Australia.
Phone 1300 884 418 03) 9580 5510 **Fax** 03) 9580 5530
Web www.rockstarsealing.com.au **Email** info@rockstarsealing.com.au

PORCELAIN SEAL

DESCRIPTION

Rockstar **PORCELAIN SEAL** helps to protect porcelain surfaces from staining due to common staining substances.

USES

Application of **PORCELAIN SEAL** on fully vitrified porcelain surfaces such as fully vitrified porcelain tiles and porcelain bathroom fittings dramatically reduces the adhesion and penetration of both water-based and oil-based staining substances. The surfaces become much easier to clean.

BENEFITS

- Does not change the surface appearance
- Excellent oil and water repellency
- Stains become easier to remove
- Ready to apply, no dilution required
- Rapid curing
- Cannot flake or peel

PROPERTIES

Appearance and colour.....	Colourless to yellowish, clear to hazy liquid
Specific Gravity (Water = 1)	0.81 g/ml
Boiling Point	120 - 200°C
Solubility in Water	Not miscible
Flash Point	30°C

APPLICATION INSTRUCTIONS

- 1) Always apply first to an inconspicuous area or scrap piece of tile to ensure the suitability of this product for your surface.
- 2) Ensure the surface to be sealed is dry and free of any oils and other surface contaminants. If in doubt cleanse thoroughly with Rockstar Neutral Cleaner, rinse with water and allow to dry.
- 3) Apply **PORCELAIN SEAL** undiluted using a lambswool applicator or low pressure hand sprayer. Ensure that the surface is fully saturated without leaving pools of material. Apply a second coat as soon as the first coat has dried (1-2 hours).
- 4) The product will cure in 12-24 hours depending on atmospheric conditions.

COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 10-14 Mt² per litre.

PRECAUTIONS

- 1) Do not allow pools of liquid **PORCELAIN SEAL** to dry on the surface. Remove any excess material with a lint-free cloth.
- 2) Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
- 3) Ensure that there are no sources of ignition in area.

CLEANING

Clean all equipment with mineral turpentine.

PACKAGING

PORCELAIN SEAL is available in 1, 5 and 20 litre packs.

STORAGE

Keep container tightly closed when not in use.

Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.

DISCLAIMER

The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.