



**BDT Pty Ltd.** Trading as **Rockstar Sealing Systems** ABN 18 085 322 390.  
**Head Office** 3 Spray Avenue, Mordialloc 3195 Victoria, Australia.  
**Phone** 1300 884 418 03) 9580 5510 **Fax** 03) 9580 5530  
**Web** www.rockstarsealing.com.au **Email** info@rockstarsealing.com.au

## STONE SHIELD

### DESCRIPTION

Rockstar **STONE SHIELD** is a clear, UV stable, low-sheen acrylic co-polymer sealer for terrazzo and stone surfaces.

### USES

**STONE SHIELD** is a long lasting and hard-wearing sealer that protects stone and terrazzo surfaces from oil, grease and other staining substances. Application of **STONE SHIELD** on coloured stones will impart an attractive low sheen finish and enhance the stone's colour.

### BENEFITS

- Provides a total barrier to oil, grease and other staining substances entering the floor
- UV stable, can be used outdoors
- Xylene-free
- Can be easily recoated

### PROPERTIES

Appearance and colour.....	Colourless liquid with hydrocarbon odour
Specific Gravity (Water = 1) .....	0.87 g/ml
Boiling Point .....	130 - 180°C
Solubility in Water .....	Not miscible
Flash Point .....	18°C

## APPLICATION INSTRUCTIONS

- 1) Always apply first to an inconspicuous area or scrap piece of flooring to ensure the suitability of this product for your flooring surface.
- 2) Ensure the surface to be coated is clean, dry and free of any oils and other surface contaminants.
- 3) Apply a first thin coat of **STONE SHIELD** by brush or roller. Do not allow sealer to pool and do not apply as a thick coat as blistering of the coating may occur.
- 4) Allow the first coat to dry (4-12 hours depending on atmospheric conditions).
- 5) Apply a second thin coat.
- 6) If required apply a third coat once the second coat is dry.

## COVERAGE

Coverage is dependent on the permeability of the surface being coated and is in the range of 8.5-11 Mt<sup>2</sup> per litre per coat

## PRECAUTIONS

- 1) Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
- 2) Ensure that there are no sources of ignition in area.

## CLEANING

Clean all equipment with mineral turpentine

## PACKAGING

**STONE SHIELD** is available in 1, 5 and 20 litre packs.

## STORAGE

Keep container tightly closed when not in use.

Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

## SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.

## DISCLAIMER

The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.