



BDT Pty Ltd. Trading as **Rockstar Sealing Systems** ABN 18 085 322 390.
Head Office 3 Spray Avenue, Mordialloc 3195 Victoria, Australia.
Phone 1300 884 418 03) 9580 5510 **Fax** 03) 9580 5530
Web www.rockstarsealing.com.au **Email** info@rockstarsealing.com.au

ANTI-GRAFFITI

DESCRIPTION

Rockstar **ANTI-GRAFFITI** is a high performance surface treatment that allows easy removal of unsightly spray can and felt-tip marker based graffiti from vertical stone surfaces.

USES

ANTI-GRAFFITI can be used on permeable stone surfaces in areas that are prone to graffiti attack. Typical application areas include external boundary walls in train stations, schools and other public buildings.

BENEFITS

- Resists the adhesion of graffiti paint and markers making the surfaces easier to clean
- Does not change the surface appearance
- Does not inhibit the water-vapour permeability
- Ready to apply, no dilution required
- Rapid curing
- Cannot flake or peel

PROPERTIES

| | |
|------------------------------------|--|
| Appearance and colour..... | Colourless liquid with petroleum odour |
| Specific Gravity (Water = 1) | 0.83 g/ml |
| Boiling Point | 120 - 200°C |
| Solubility in Water | Not miscible |
| Flash Point | 30°C |

APPLICATION INSTRUCTIONS

- 1) Always apply first to an inconspicuous area or scrap piece of wall cladding to ensure the suitability of this product for your wall surface.
- 2) Ensure the surface to be sealed is dry and free of any oils and other surface contaminants.
- 3) Apply **ANTI-GRAFFITI** undiluted using a low pressure hand sprayer or a lambswool applicator. Allow this first coat to dry for around 1 hour.
- 4) Apply a further 2 coats allowing 1 hour drying time between coats.
- 5) The product will cure in 12-24 hours depending on atmospheric conditions.

COVERAGE

Coverage is dependent on the permeability of the wall surface and is in the range of 5-15 Mt² per litre.

REMOVAL OF GRAFFITI

It is important that the graffiti removal process be initiated as soon as possible as graffiti tends to “bake on” over time and becomes harder to remove.

Graffiti can be removed by cleaning the affected surface with hot high-pressure water or by the application of Rockstar **MIRACLE CLEAN**. Once the cleaned surfaces are dry, reapply **ANTI-GRAFFITI** as per the above application instructions.

PRECAUTIONS

- 1) Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
- 2) Ensure that there are no sources of ignition in area.

CLEANING

Clean all equipment with mineral turpentine.

PACKAGING

ANTI-GRAFFITI is available in 1, 5 and 20 litre packs.

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children. Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.

DISCLAIMER

The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.