



BDT Pty Ltd. Trading as **Rockstar Sealing Systems** ABN 18 085 322 390.
Head Office 3 Spray Avenue, Mordialloc 3195 Victoria, Australia.
Phone 1300 884 418 03) 9580 5510 **Fax** 03) 9580 5530
Web www.rockstarsealing.com.au **Email** info@rockstarsealing.com.au

WATER BASED STRIPPER

DESCRIPTION

Rockstar **WATER BASED STRIPPER** is a stripping solution that easily removes polishes from floor surfaces.

USES

WATER BASED STRIPPER is formulated to remove water-based crosslinked acrylic coatings and polishes from natural stone, concrete, terracotta and porcelain with a minimum of effort.

- Quickly softens and emulsifies old, worn or discoloured finishes
- Easily cuts through highly built-up or heavily burnished finishes.
- Water-based formulation

PROPERTIES

Appearance and colour	Colourless to slightly yellow liquid with amine odour
pH	11.5-12.5
Specific Gravity (Water = 1)	0.97 g/ml
Boiling Point	100°C
Solubility in Water	Miscible
Flash Point	67°C

APPLICATION INSTRUCTIONS

- 1) Always apply first to an inconspicuous area to ensure the suitability of this product for your floor.
- 2) Dilute **WATER BASED STRIPPER** 1:4 with hot water and apply liberally to the floor area with a mop. Work in small manageable sized areas.
- 3) Allow the solution to remain on the floor a minimum of 10 minutes to soften and emulsify the coating.
- 4) Agitate the floor area with a floor scrubber or a stiff bristle broom to dislodge and solubilise the old coating.
- 5) Pick up the residue. If required, repeat the application process until all traces of coating is removed.
- 6) Once all old coating has been removed, rinse the floor area with Rockstar **NEUTRAL CLEANER**.

PRECAUTIONS

- 1) This solution is corrosive; avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
- 2) Use in a well ventilated area.

PACKAGING

WATER BASED STRIPPER is available in 1, 5 and 20 litre packs.

STORAGE

Keep container tightly closed when not in use.

Store in a cool, dry place out of reach of children.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.

DISCLAIMER

The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.