

TECHNICAL DATA SHEET

STONE ENHANCER



DESCRIPTION

Rockstar STONE ENHANCER is sealer that darkens and brings out the natural beauty of stone. Ideal for enriching the colour of faded dark stones.

USES

STONE ENHANCER is used to permanently darken and enhance the colour of stone and tile surfaces. The surfaces also become highly resistant to the penetration of water.

Can be used on Bluestone tiles, Concrete Pavers, Porcelain tiles and Marble tiles.

BENEFITS

- Long lasting and weather-resistant
- Can even out colour inconsistencies
- The surface becomes highly water repellent
- UV Stable

PROPERTIES

Appearance and colour	Colourless to yellowish, clear to hazy liquid
Specific Gravity (Water = 1).....	0.85 g/ml
Boiling Point.....	120 - 200°C
Solubility in Water.....	Not miscible
Flash Point.....	31°C

APPLICATION INSTRUCTIONS

1. A sample before applying is highly recommended
2. Ensure the surface to be sealed is free of excess grout and grout haze, is dry and free of any oils and other surface contaminants.
3. Apply STONE ENHANCER using a lambswool applicator. Ensure that the surface is fully saturated without leaving pools of material. Remove excess material on the surface with a clean cloth. Rub the product into the stone.
4. Apply 2 more coats. Ensure you rub sealer into stone. Leave no residue on the surface. More coats maybe required.
5. The product will dry in 6-8 hours, full cure develops after 7 days.

COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 6-15 Mt² per litre.

PRECAUTIONS

1. Do not allow pools of liquid STONE ENHANCER to dry on the surface.
2. Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
3. Ensure that there are no sources of ignition in area.

CLEANING

Clean all equipment with mineral turpentine.

PACKAGING

STONE ENHANCER is available in 1, 5 and 20 litre containers.

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.