

TECHNICAL DATA SHEET
PAVER SEAL



DESCRIPTION

Rockstar PAVER SEAL is a clear, UV stable, solvent-based acrylic sealer. Rockstar Paver Seal will apply a sacrificial coating on the surface.

USES

PAVER SEAL is a durable surface sealer which protects stone, slate and concrete surfaces from oil and grease stains.

BENEFITS

- UV stable, can be used outdoors
- Provides a barrier to oil and grease entering the floor
- Imparts a glossy "wet look"

PROPERTIES

Appearance and colour.....	Colourless liquid with petroleum odour
Specific Gravity (Water = 1).....	0.93 g/ml
Boiling Point.....	155 - 175 °C
Solubility in Water.....	Not miscible
Flash Point.....	30 °C

APPLICATION INSTRUCTIONS

1. Ensure the surface to be coated is clean, dry and free of any oils and other surface contaminants.
2. Apply an even coat of PAVER SEAL by brush or roller. First coat can be diluted by 25% with Thinners to provide a foundation for further coats
3. Allow the first coat to dry (1-3 hours depending on atmospheric conditions).
4. Apply a second even coat.
5. If required apply a third coat once the second coat is dry.

COVERAGE

Coverage is dependent on the permeability of the surface being coated and is in the range of 5-10 Mt² per litre per coat.

PRECAUTIONS

Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.

CLEANING

Clean all equipment with Xylene.

PACKAGING

PAVER SEAL is available in 1, 5 and 20 litre packs.

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia.

For further detailed information refer to Material Safety Data Sheet.