

TECHNICAL DATA SHEET

ANTI-SLIP



DESCRIPTION

Rockstar ANTI-SLIP is a treatment that increases the coefficient of friction of wet floor surfaces. The treatment is not a coating and will not change the appearance of the surface.

USES

Rockstar Anti-Slip produces a micro etch of the surface. This provides increased slip protection in wet conditions.

Ideal for Terrazzo, Marble, Porcelain tiles and Glazed Ceramic tiles.

ANTI SLIP should only be applied by authorised Rockstar applicators.

BENEFITS

- Dramatically reduces the slipperiness of wet floors
- Does not change the appearance of the surface
- Compatible with subsequent penetrating sealers
- Is **NOT** a surface coating

PROPERTIES

Appearance and colour	Colourless to slightly yellow aqueous liquid
pH	2
Specific Gravity (Water = 1)	Approx. 1 g/ml
Boiling Point	100 °C
Solubility in Water	Miscible
Flash Point	Non-flammable

APPLICATION INSTRUCTIONS

1. Always test on a sample tile to determine dilution ratio and dwell time to achieve the desired slip rating.
2. First wet the floor with water. Dilute Rockstar Anti-Slip with water and apply to affected area. Move around with a doodle bug
3. Leave solution on the floor for the appropriate dwell time
4. Treat no more than 20-30sqm at a time
5. Then remove with a wet vacuum. Rinse well using Rockstar Neutral Cleaner
6. Seal the floor with ROCKSTAR NATURAL FINISH STONE SEALER or ROCKSTAR GREEN STAR SEALER.

COVERAGE

Coverage range rate is 20-30sqm per litre. This is guide only

PRECAUTIONS

1. ANTI SLIP should only be applied by authorised Rockstar applicators.
2. This product is corrosive. Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
3. Avoid contact of ANTI SLIP with aluminium and other metal surfaces. (Protect them with tape.)



CLEANING

Clean all equipment in water

PACKAGING

ANTI SLIP is available in 5 and 20 litre containers.

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.