

1300 88 44 18 3 Spray Avenue Mordialloc, VIC 3195, Australia R O C K S T A R S E A L I N G . C O M . A U

TECHNICAL DATA SHEET GLOSS SLATE SEAL



DESCRIPTION

Rockstar GLOSS SLATE SEAL is a clear, UV stable, solvent-based acrylic sealer. Rockstar GLOSS SLATE SEAL will apply a sacrificial coating on the surface leaving a glossy wet look finish. Ideal for use on Slate and Concrete floors.

USES

GLOSS SLATE SEAL is a durable surface sealer which protects, Slate and Concrete surfaces from oil and grease stains. Can be used indoors and outdoors.

BENEFITS

- UV stable, Non yellowing and can be used outdoors
- Provides a barrier to oil and grease entering the floor
- Imparts a glossy "wet look"
- High solids formulation for long life

PROPERTIES

| Appearance and colour | Colourless liquid with petroleum odour |
|------------------------------|--|
| Specific Gravity (Water = 1) | 0.93 g/ml |
| Boiling Point | 155 - 175°C |
| Solubility in Water | Not miscible |
| Flash Point | 30 ° C |

APPLICATION INSTRUCTIONS

- 1. Ensure the surface to be coated is clean, dry and free of any oils and other surface contaminants.
- 2. Apply an even coat of GLOSS SLATE SEAL by brush or roller. First coat can be diluted by 25% with Thinners to provide a foundation for further coats.
- 3. Allow the first coat to dry (1-3 hours depending on atmospheric conditions).
- 4. Apply a second even coat.
- 5. If required apply a third coat once the second coat is dry.

COVERAGE

Coverage is dependent on the permeability of the surface being coated and is in the range of $6-10 \text{ Mt}^2$ per Litre per coat.

PRECAUTIONS

Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear. Wear a Breathing Mask, using solvent vapor filters.

CLEANING

Clean all equipment with Xylene.

PACKAGING

GLOSS SLATE SEAL is available in 1, 5, 20 Litre Containers

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to

Material Safety Data Sheet.

DISCLAIMER: The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.