

TECHNICAL DATA SHEET

# LIFT OFF



## DESCRIPTION

Rockstar LIFT OFF is an acid based cleaner formulated to remove grout stains, cement haze, lime deposits and efflorescence. Do not use on ACID SENSITIVE natural stones. Such as Limestone, Marble, Terrazzo and polished porcelain.

## USES

Use LIFT OFF to clean Bluestone tiles, Porcelain tiles, Concrete Pavers and ceramic tiles. **DO NOT** use on acid-sensitive substrates such as Limestone, Marble, Terrazzo and polished porcelain.

## BENEFITS

- Dissolves cement-based haze and residue.
- Safer to use than Hydrochloric acid
- No fumes
- Can be used to remove rust

## PROPERTIES

Appearance and colour.....	Colourless liquid
Specific Gravity (Water = 1).....	1.22 g/ml
Boiling Point.....	100 °C
Solubility in Water.....	Miscible
pH.....	<2
Flash Point.....	Non-flammable

## APPLICATION INSTRUCTIONS

1. Always use rubber gloves and protective goggles when using this product
2. Read the instructions carefully
3. Always apply first to an inconspicuous area to gauge the suitability of this product for your substrate.
4. Pre-wet the surface with water before application.
5. Dilute LIFT OFF with up to 4 parts water depending on the degree of cleaning required.
6. Apply the diluted solution and allow it to contact the surface for 3-5 minutes after which the surface should be agitated with a doodle bug or scrubbed with an buffing machine. Do not allow the solution to dry on the surface.
7. Mop or wet vacuum the surface to remove slurry. Rinse thoroughly with clean water to remove any excess cleaning solution.

## PRECAUTIONS

1. This product is corrosive!
2. Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
3. Use with caution around metal surfaces, carpet and rendered cement surfaces

### CLEANING

Clean all equipment with water.

### PACKAGING

LIFT OFF is available in 5 and 20 Litre Containers / 1.32Gal / 5Gal.

### STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

### SAFETY

Classified as Hazardous according to criteria of Worksafe Australia.

For further detailed information refer to Material Safety Data Sheet.