

TECHNICAL DATA SHEET

ANTI-GRAFFITI



DESCRIPTION

Rockstar ANTI-GRAFFITI is a high performance solvent based penetrating sealer which protects against Graffiti attack. It does not alter the appearance of the stone. Ideal for Bluestone , cladding , Travertine,, sandstone and cement render.

USES

ANTI GRAFFITI can be used on NATURAL STONE surfaces in areas that are prone to graffiti attack. Typical application areas include external boundary walls in train stations, schools, House fences and office buildings. Can be used on Bluestone, travertine, sandstone, and cement render.

BENEFITS

- Resists the adhesion of graffiti paint and markers making the surfaces easier to clean
- Does not change the surface appearance
- Ready to apply, no dilution required
- Rapid curing
- UV stable

PROPERTIES

Appearance and colour.....	Colourless liquid with petroleum odour
Specific Gravity (Water = 1).....	0.83 g/ml
Boiling Point.....	120 - 200 °C
Solubility in Water.....	Not miscible
Flash Point.....	30 °C

APPLICATION INSTRUCTIONS

1. Ensure the surface to be sealed is dry and free of any oils and other surface contaminants.
2. Apply ANTI-GRAFFITI undiluted using a low pressure hand sprayer or a lambswool applicator. Allow this first coat to dry for around 1 hour.
3. Apply a further 2 coats allowing 1 hour drying time between coats.
4. The product will cure in 12-24 hours depending on atmospheric conditions.

COVERAGE

Coverage is dependent on the permeability of the wall surface and is in the range of 6-15 Mt² per Litre/5-150sq ft per Quart.

REMOVAL OF GRAFFITI

It is important that the graffiti removal process be initiated as soon as possible as graffiti tends to "bake on" over time and becomes harder to remove.

Graffiti can be removed by cleaning the affected surface with hot high-pressure water in combination with Rockstar MIRACLE CLEAN. Once the affected areas are cleaned, reapply ANTI-GRAFFITI as per the above application instructions.

PRECAUTIONS

Avoid contact with skin and eyes by wearing suitable PPE gear. Breathing mask, Eye ware and gloves.

CLEANING

Clean all equipment with mineral turpentine.

PACKAGING

ANTI-GRAFFITI is available in 1, 5, 20 Litre Containers / 1 Quart / 1.32Gal / 5Gal.

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia.

For further detailed information refer to Material Safety Data Sheet.