

TECHNICAL DATA SHEET

# BLUESTONE SEALER



## DESCRIPTION

ROCKSTAR BLUESTONE SEALER is a high-performance Solvent Based Penetrating Sealer which offers superior protection from water and oil-based contaminants. ROCKSTAR BLUESTONE SEALER has been formulated using the latest in Stone Sealing Technology. Developed for Bluestone, Basalt, Granite, Porcelain tiles and Polished Concrete.

## USES

Application of BLUESTONE SEALER enhances the stain resistance of the surface. The ingress of staining substances is retarded, making the surface easier to clean.

BLUESTONE SEALER can be used on Bluestone, Basalt, Granite, Porcelain Tiles and Polished Concrete.

Can be used in both domestic and commercial applications

## BENEFITS

- Excellent oil and water repellency
- Excellent penetration into dense substrates
- Minimal change in the appearance of the stone
- Does not inhibit the water-vapour permeability
- Rapid curing
- UV Stable

## PROPERTIES

Appearance and colour.....	Colourless to yellowish, clear to hazy liquid
Specific Gravity (Water = 1).....	0.83 g/ml
Boiling Point.....	120 - 200°C
Solubility in Water.....	Not miscible
Flash Point.....	30°C

## APPLICATION INSTRUCTIONS

1. Ensure the surface to be sealed is free of excess grout and is dry and free of any oils and other surface contaminants.
2. Apply BLUESTONE SEALER undiluted by lambswool applicator or low pressure hand sprayer. Ensure that the surface is fully saturated without leaving pools of material.
3. Apply a second coat once the first coat has dried (1-2 hours).
4. The product will cure in 24 hours depending on atmospheric conditions.

## COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 10-15 Mt<sup>2</sup> per Litre/50-150 ft<sup>2</sup> per Quart.

## PRECAUTIONS

1. Do not allow pools of liquid BLUESTONE SEALER to dry on the surface. Remove excess liquid with a clean, lint-free cloth.
2. Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.

### CLEANING

Clean all equipment with mineral turpentine.

### PACKAGING

BLUESTONE SEALER is available in 1, 5 and 20 Litre Containers / 1 Quart / 1.32Gal / 5Gal.

### STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

### SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.