

TECHNICAL DATA SHEET

# STONE ENHANCER



## DESCRIPTION

Rockstar STONE ENHANCER is a sealer that darkens and brings out the natural beauty of stone. Ideal for enriching the colour of worn, faded or damaged stone.

Rockstar STONE ENHANCER is a penetrating and breathable sealer which is suitable for use indoors and outdoors.

## USES

Rockstar STONE ENHANCER is used to darken and enhance the colour of stone and tile surfaces.

New formula now boasts superior protection against oil and waterbased contaminants

Can be used on Natural Stone, Terrazzo, Concrete Pavers and Porcelain Tiles.

Suitable for indoor and outdoor use.

## BENEFITS

- Long lasting and weather-resistant
- Can even out colour inconsistencies
- The surface becomes highly resistant to oil and waterbased contaminants
- UV Stable

## PROPERTIES

|                                   |   |
|-----------------------------------|---|
| Appearance and colour .....       | Colourless to yellowish, clear to hazy liquid |
| Specific Gravity (Water = 1)..... | 0.85 g/ml                                     |
| Boiling Point.....                | 120 - 200°C                                   |
| Solubility in Water.....          | Not miscible                                  |
| Flash Point.....                  | 31°C  |

## APPLICATION INSTRUCTIONS

1. A test sample before applying is highly recommended
2. Ensure the surface to be sealed is free of excess grout and grout haze, is dry and free of any oils and other surface contaminants.
3. Apply STONE ENHANCER using a lambswool applicator. Ensure that the surface is fully saturated without leaving pools of sealer. Remove excess sealer on the surface with a clean dry cloth. Rub the product into the stone.
4. Apply 2 more coats. Ensure you rub sealer into stone. Leave no residue on the surface. More coats maybe required.
5. The product will dry in 6-8 hours, full cure develops after 7 days.

## COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 6-15 Mt<sup>2</sup> per Litre / 50 -150ft<sup>2</sup> per Quart.

## PRECAUTIONS

1. Do not allow pools of liquid STONE ENHANCER to dry on the surface.
2. Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.

### CLEANING

Clean all equipment with mineral turpentine.

### PACKAGING

STONE ENHANCER is available in 1, 5 and 20 Litre Containers / 1 Quart / 1.32Gal / 5Gal.

### STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

### SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.