

**TECHNICAL DATA SHEET** 

# **TIME SAVER**



## DESCRIPTION

Rockstar TIME SAVER is a water-based Pre-Sealing solution formulated for use on Natural Stone Paving, Concrete Pavers and Terrazzo.

#### **USES**

TIME SAVER is applied to the stone or tile surface prior to grouting to reduce permeability and increase the stain resistance of the surface. Excess grout generated during the grouting process can then be easily removed.

## **BENEFITS**

- · Environmentally friendly water-based formulation
- · Reduces the ingress of water borne staining substances
- Does not inhibit the water-vapour permeability
- Allows grout haze to be easily removed from the stone's surface
- · Rapid curing
- Zero VOC
- UV stable
- · Excellent water repellent

## **PROPERTIES**

Appearance and colour	Milky white liquid
pH	7-8
Specific Gravity (Water = 1)	0.98 g/ml
Boiling Point	100°C
Solubility in Water	Miscible
Flash Point	Non flammable

## **APPLICATION INSTRUCTIONS**

- 1. Ensure the surface to be sealed is clean, dry and free of any oils and other surface contaminants.
- 2. Apply TIME SAVER with a lambswool applicator or a low pressure hand sprayer. Ensure an even coat has been applied to the stone surface.
- 3. The product will cure in around 12 hours depending on atmospheric conditions.

## COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 6-15 Mt<sup>2</sup> per Litre / 50 -150ft<sup>2</sup> per Quart.

## **PRECAUTIONS**

Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.

## **CLEANING**

Clean all equipment in water.

## **PACKAGING**

TIME SAVER is available in 5 and 20 Litre Containers / 1.32Gal / 5Gal.

## **STORAGE**

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

## **SAFETY**

Classified as Non-Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.

**DISCLAIMER:** The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.