

TECHNICAL DATA SHEET

CONCRETE SEAL



DESCRIPTION

Rockstar CONCRETE SEAL is a water-based acrylic sealer for concrete and masonry surfaces. Referred to as a sacrificial coating. Rockstar Concrete Seal is VOC free and leaves a LOW SHEEN finish. Recommended for terrazzo, terracotta, natural stone and concrete surfaces.

USES

Application of CONCRETE SEAL on concrete and masonry surfaces provides a durable coating, which provides protection from oil and grease based contaminants. Ideal for use on terrazzo, terracotta, natural stone and concrete surfaces. Can also be used in carparks and factories for dust management.

BENEFITS

- Protects surfaces from the spillage of oil, grease and foods.
- Environmentally friendly with no VOC content.
- Imparts a LOW SHEEN finish.

PROPERTIES

Appearance and colour.....	Milky liquid
pH.....	6-8
Specific Gravity (Water = 1).....	1.02 g/ml
Boiling Point.....	100° C
Solubility in Water.....	Miscible
Flash Point.....	Non flammable

APPLICATION INSTRUCTIONS

1. Ensure the surface to be sealed is clean, dry and free of any oils and other surface contaminants.
2. Apply CONCRETE SEAL using a damp lambswool applicator. Apply an even coat over the floor.
3. When applying first coat of ROCKSTAR CONCRETE SEAL dilute 50:50 with water. Subsequent coats are FULL STRENGTH.
4. Allow a minimum of 1 hour before applying further coats. Usually 3-5 coats are required.

COVERAGE

Coverage is dependent on the permeability of the surface. The first coat usually covers around 15Mt² per Litre, subsequent coats should cover 20 Mt² per Litre / 215-250sq foot per Quart.

PRECAUTIONS

Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.

CLEANING

Clean all equipment in water.

PACKAGING

CONCRETE SEAL is available in 5 and 20 Litre Containers / 1.32Gal / 5Gal.

STORAGE

Keep the container tightly closed when not in use. Store in a cool, dry place out of reach of children.

SAFETY

Classified as Non-Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.