

TECHNICAL DATA SHEET SPRAY SEAL



DESCRIPTION

ROCKSTAR SPRAY SEAL is a fast penetrating stain inhibitor to seal tiles, stone and grout. Simple, safe and easy spray sealant for terracotta, granite, sandstone, aggregate stone, porcelain, grout, marble and limestone.

USES

ROCKSTAR SPRAY SEAL is suited to tile, stone and grout surfaces. Protects and seals: terracotta, granite, sandstone, aggregate stone, porcelain, grout, marble, limestone.

BENEFITS

- Quickly penetrates surfaces and inhibits stain absorption
- Simple, safe and easy spray sealant application
- Non yellowing and UV resistant

APPLICATION INSTRUCTIONS

1. Always test on a small inconspicuous area first.
2. Ensure the surface to be sealed is clean, dry and free of any oils, paint, grease, traces of grout and other surface contaminants.
3. Spray ROCKSTAR SPRAY SEAL to the area in a sweeping action from a distance of approximately 15-20cm away.
4. A second application may be applied after 4 hours.
5. Allow 24 hours for sealant to fully cure before allowing full use of the treated area.

COVERAGE

Between 10-18m² per can depending on the porosity of the surface.

ROUTINE CLEANING

To preserve maximum efficiency we recommend using Rockstar Neutral Stone Cleaner or Rockstar Stone Clean Plus for all routine cleaning of grout, stone and tile surfaces.

PRECAUTIONS

ROCKSTAR SPRAY SEAL should only be used in an open or well ventilated area, or when a suitable respirator is worn. Any spill should be removed immediately to minimise absorption.

CLEANING

Clean all equipment in water.

PACKAGING

ROCKSTAR SPRAY SEAL is available in 300g aerosol can.

STORAGE

Keep container tightly closed when not in use.
Store in a cool, dry place out of reach of children.

CAUTION

HIGHLY FLAMMABLE. Do not pierce or burn even when empty. Dispose of in garbage or at an appropriate recycling collection point. Store below 50°C. Do not spray on naked flame.